

# GoPal® E24

The **GoPal** AMR solution from Robotize sets new standards for versatility, efficiency and safety in automated material transportation



# TECHNICAL SPECIFICATIONS

## GoPal<sup>®</sup> E24

---

### APPLICATION

Autonomous Mobile Robot (AMR) for automatically picking up, transporting and delivering standard Euro-pallets/half Euro-pallets with medium-to-heavy payload (max. 1000 kg).

---

### DIMENSIONS

|                         |                     |
|-------------------------|---------------------|
| Length x Width x Height | 1400 x 860 x 340 mm |
| Mass                    | 187 kg              |

---

### PERFORMANCE

|                                    |                      |
|------------------------------------|----------------------|
| Battery time (autonomy)            | 6-14 hours or 20 km* |
| Maximum speed                      | 2,4 m/s (8,6 km/h)*  |
| Turning radius (from robot centre) | 950 mm               |

---

### SAFETY

- Laser scanners (360° protection)
  - Mechanical bumper (360° protection)
  - 4 x emergency stop buttons
- 

### ADDITIONAL OBSTACLE AVOIDANCE SENSORS

3 x 3D cameras (two front facing and one rear facing)

---

### BATTERY

|                   |                            |
|-------------------|----------------------------|
| Type / Voltage    | LiFePO <sub>4</sub> / 48 V |
| Charge time       | 45 minutes (full charge)   |
| Number of charges | About 5000                 |

---

### CHARGER INTERFACE

- Automatic docking interface (at robot front)
- Connector for manually charging (at robot rear)

# TECHNICAL SPECIFICATIONS

## GoPal<sup>®</sup> E24

---

### COMMUNICATION

Wi-Fi 802.11ac

---

### ENVIRONMENTAL

Operating temperature -10°C to +45 °C  
Humidity (max.) 95% (non-condensing)

---

### FLOOR REQUIREMENTS

Slope average (max.) Near-level (2 %)  
Friction coefficient (min.) 0,60  
Edge height (max.) 4 mm

---

### LOAD

Payload (max.) 1000 kg  
Length (max.) 1240 mm  
Width (max.) 820 mm  
Height (max.) 2400 mm\*

---

### PALLET TYPES

Standard Euro-pallets and Standard half Euro-pallets. Others on inquiry.

---

### PALLET CONDITION

Undamaged, original strength maintained (grade A or B)

---

### LANE CONDITIONS

Minimum lane width 1200 mm  
Recommended lane width 2100 mm  
High speed lane width 2800 mm

---

*\*depending on load conditions.*

*Due to a policy of continued product development Robotize reserves the right to alter or amend any specification without notice.*

# robotize



Advanced internal logistics  
made safe and simple

[www.robotize.com](http://www.robotize.com)